

T-Handle 6-Point Socket Wrenches

PN	DESC
TW12-10L	5/16" X 12"
TW12-12L	3/8" X 12"
TW12-14L	7/16" X 12"
TW12-16	1/2" X 12"
TW12-16L	1/2" X 12"
TW-12-16-16L	1/2" X 16"
TW12-18L	9/16" X 12"
TW12-18-18L	9/16" X 18"
TW12-33-18L Fl.	9/16" X 33"
TW12-20L	5/8" X 12"
TW12-22L	11/16" X 12"
TW12-24L	3/4" X 12"
TW12-26L	13/16" X 12"
TW12-18L	7/8" X 12"
TW12-30L	15/16" X 12"
TW12-32L	1" X 12"

- Hardened American Steel
- Solid Core Handle provides superior grip and rigid construction limiting twisting and flexing, and distributing pressure evenly throughout gloved hand.
- Deep wall and hollow shank
- Custom lengths available
- Made in USA



TW12-16L

PN	DESC
TW38-DR	3/8" Square Drive X 7"
TW38DR-12	3/8" Square Drive X 12"
TW12-DR	1/2" Square Drive X 10-1/2"

- Hardened American Steel
- Solid Core Handle provides superior grip and rigid construction limiting twisting and flexing, and distributing pressure evenly throughout gloved hand.
- Made in USA



TW12-DR

T-Handle Drives

PN	DESC
BB14-5	1/4" Drive, 5-3/4" Length
BB38-8	3/8" Drive, 8 1/2" Length
IBB38-9-19M	3/8" Drive, 9" Length, 19mm Socket
IBB38-12	3/8" Drive, 12" Length
BB38-15	3/8" Drive, 15" Length
IBB38-15	3/8" Drive, 15" Length
BB12-12	1/2" Drive, 12" Length
BB12-17	1/2" Drive, 17" Length
BB34-22	3/4" Drive, 22" Length



IBB38-8

Breaker Bars

Break loose stubborn nuts and bolts without damage your socket wrench! The additional length allows the same amount of force to generate more torque than a standard length socket wrench. Custom sizes available.

RATED 1000 VAC / 1500 VDC Tested to 10,000 VAC and Rated for 1,000 VAC when working on or around live parts