

# Torque Wrenches

- Audible "click" and/or a few degrees of travel provide simple, fast indication of micrometer - accurate torque settings.
- Low friction torque control mechanism produces accurate readings in either direction.
- Accuracy is +/-4% of setting right hand (clockwise) and +/-6% of setting left hand (counterclockwise) within upper 80% of scale.
- Two calibration adjustments (major and fine) permit easy and precise torque settings. Most conventional torque wrenches have only one adjustment.
- Dual scale models give readings in Inch-Pounds/Newton Meters or Foot-Pounds/Newton Meters.
- Spring-loaded or Twist-locking collar locks scale on desired reading and remains in locked position. Wrench cannot be left inadvertently unlocked.
- Heavy-Duty, reversible ratchet models have quick-shift lever to allow easy single-hand shifting.
- Always store all adjustable models at their lowest torque setting.



## 1/4" Square Drive DESC \_\_\_\_\_

1050TW14I.....	10-50 Inch Lbs.
30150TW14I.....	30-150 Inch Lbs.
30200TW14I.....	30-200 Inch Lbs.

## 3/8" Square Drive DESC \_\_\_\_\_

30150TW38I.....	30-150 Inch Lbs.
30150TW38I-K.....	30-150 Inch Lbs. in Protective Case
30150TW38I-NR.....	30-150 Inch Lbs. with Non-Ratcheting Head
30200TW38I.....	30-200 Inch Lbs.
30200TW38I-K.....	30-200 Inch Lbs. in Protective Case
50250TW38I.....	50-250 Inch Lbs.
150750TW38I.....	150-750 Inch Lbs.
1575TW38F.....	15-75 Foot Lbs.
1575TW38F-K.....	15-75 Foot Lbs. in Protective Case
30150TW38F.....	30-150 Foot Lbs.

## 1/2" Square Drive DESC \_\_\_\_\_

150750TW12I.....	150-750 Inch Lbs.
1575TW12F.....	15-75 Foot Lbs.
25250TW12F.....	25-250 Foot Lbs.
30150TW12F.....	30-150 Foot Lbs.

30150-30200TW BOOT.... Replacement boot for 30150 and 30200



30200TW38I



25250TW12F



30150TW38I

# Torque Screwdrivers



236TSDK

- Precision micrometer scale calibrated in Inch-Pounds, increments 1 inch-lbs.
- Easy-release bit holders featuring 1/4" female hex drive securely retain bits during operation while permitting easy removal.
- Anti-backlash design for repeatability.
- Meets or exceeds ASME B107.14M and ISO 6789 specifications.
- Adjustable model accuracy is +/-6 of setting, starting at 20% of full scale. Right hand (clockwise) only.



## PN \_\_\_\_\_ DESC \_\_\_\_\_

236TSD.....	2-36 Inch Lbs.
236TSDK.....	2-36 Inch Lbs. in Protective Case
236TSD140.....	2-36 Inch Lbs. 1/4" Square Drive

235TSD BOOT... 236TSD Replacement Boot

RATED 1000 VAC / 1500 VDC  
Tested to 10,000 VAC and Rated for 1,000 VAC when working on or around live parts