

Fuse Pullers

- Convenient for removing or replacing cartridge-type fuses
- PFP-0, PFP-1, and PFP-3:
 - No slip grip including notched handles
 - High dielectric glass-filled polypropylene
- PFP-0G and PFP-2G:
 - High impact nylon for greater strength
 - No-slip gripping surface and protective finger guards



Specifications	PFP-0	PFP-0G	PFP-1	PFP-2G	PFP-3
Length	5-1/8"	4-9/16"	7-5/8"	7-3/8"	11-5/8"
Fuse Diameter	9/32" - 1/2"	1/4" - 1/2"	1/2" - 1"	9/16" - 1"	3/4" - 2-1/2"
Dielectric Rating	1000V*	1000V*	1000V*	1000V*	1000V*
Guarded	No	Yes	No	Yes	No


Yes, they are RATED! You can use them anywhere with their 1000 VAC / 1500V DC rating. We fully tested them per ASTM F1505*.



Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V