

Telescopic Hot Sticks



CLOSE-UP: Universal Head with Disconnect Stick Adapter

Telescopic hot sticks offer long reach, speed, convenience and safety tested 100% per ASTM F-711. Fabricated of reinforced high density electrical grade fiber glass laminate for greater strength and dielectric properties. Cushioned cap protects base end.

Triangle shape enables each section to “lock in automatically” eliminating twisting and turning to lock sections and provides an ergonomic design with a “better gripping” surface for better control.

Fluorescent tip section is highly visible and has a foam core. All tip sections are 1.15” diameter.



CLOSE-UP: Universal Disconnect Hook

Larger share shape lock buttons are easy to operate with and without gloves.

Versatility built in by using only the number of sections required. Tool height (length) can be reduced by depressing the lock button and sliding the bottom sections off. Allowing for a lightweight tool to perform the work easier.

Easy disassembly by depressing the lock button and sliding a section, or sections, out without the use of additional tools.

Part Number	Description	Weight
CPTS-208	8' Extended Length: 1.75" Base Diameter (26" Retracted)	3.0 lbs
CPTS-212	12' 7" Extended Length: 1.45" Base Diameter (58" Retracted)	3.7 lbs
CPTS-216	16' 9" Extended Length: 1.61" Base Diameter (60" Retracted)	5.0 lbs
CPTS-220	21' Extended Length: 1.75" Base Diameter (62" Retracted)	6.4 lbs
CPTS-225	25' 6" Extended Length: 1.91" Base Diameter (64" Retracted)	8.1 lbs
CPTS-230	30' Extended Length: 2.07" Base Diameter (66" Retracted)	10.0 lbs
CPTS-235	35' Extended Length: 2.22" Base Diameter (68" Retracted)	12.1 lbs
CPTS-240	39' 6" Extended Length: 2.38" Base Diameter (69" Retracted)	14.4 lbs
CPTS-245	44' 5" Extended Length: 2.54" Base Diameter (72" Retracted)	18.13 lbs