

PRODUCT OFFERING UPDATE BULLETIN Torque Wrenches

August 16, 2023

In catalog update preparations we were updating our torque wrench chart. We have improved the data that can be easily identified and opted to update to our part numbering structure to reflect that the available range that can be utilized is the part number. Only a few series existed where the range was different, so we wanted to align the naming convention for simplicity's sake. The first example would be our torque screwdriver, we called this our 236TSD series however the actual working range is 6-36 inch-pounds, so we've renamed this part to be our 636TSD. Aligned with this convention change, our 575TW series really works at 15-75 inch-pounds so that too has been renamed to our 1575TW series. We are keeping it easy for you - when these parts are entered on orders in our system, they will be defaulted to flip to the newly identified part numbers.

Discontinued Part #	Discontinued Product Description	UPC Code	Replacement Part #	Replacement Product Description	UPC Code
236TSD	2-36 In-Lbs Torque SD	696812000163	636TSD	6-36 In-Lbs Torque SD	696812153425
575TW38F	3/8" SqDr 15-75 Ft-Lbs TW	696812100122	1575TW38F	3/8" SqDr 15-75 Ft-Lbs TW	696812153586

Please review the [entire chart](#) representing our extensive precision torque wrench offering. It doesn't show the information as shown above but rather the entire offering and the details you want and need to know to have the right torque wrench to do the job.

In the review of the torque offerings were faced with a crossroads in early 2022 when our supplier

informed us that we would no longer be able to purchase the style featuring the compact head that we have had for over 40 years as our 30150TW series. However, in the last two months we secured this series in our permanent catalog. Of course, we had already proceeded with developing our innovative X-Drive Head into this 30150TW series. We had to have the products you needed to work safely! The good news is that there are now multiple options available for you when ordering! We have two options available for the 3/8" Square Drive (our X-Drive which is now utilizing the old part number and if you want that compact head, we've created our 30150UTW series. We will also offer the X-Drive head for our 1/4" Square Drive in this series as well, again following the same naming conventions. In both square drives there are discernable body dimensions differences, the X-Drive head being larger. It is important to note that the X-Drive can use both our booted and unbooted sockets.

30-150 In-Lb Torque Wrench Options

Our newest style features our innovative X-Drive Head. We were told we wouldn't be able to get that older style with the compact head. We were able to negotiate keeping it in our permanent catalog, but the replacement/evolution still had to be designed. We now have two options available for the 3/8" SqDr and coming soon for 1/4" SqDr.

30150TW38I (X-Drive)

30150UTW38I (Compact)

Insulated Length:	12.5"	10"
Insulated Head Depth:	2.6"	1.75"

X-Drive can use both booted and unbooted sockets.

30150UTW38I (Compact Head)

30150TW38I (X-Drive Head)

If you have any questions or for more information about orders or the availability of any of these products, please contact Customer Service at 1-800-654-1292. Thank you for your understanding and we appreciate your ongoing support.

Part Number	Description	Range/Scale					Square Drive			Tang/Lever Style				Drive Style		
		Size	In. Lb.	Ft. Lb.	Nm	Preset	1/4"	3/8"	1/2"	Std	Low	CW	CCW	X Drive	Short	Fixed
636TSD	6-36 In-Lbs Torque SD	6-36	*													Power Bits
636TSD140	6-36 In-Lbs Torque SD w/Boot	6-36	*													Power Bits
636TSD-K	6-36 In-Lbs Torque SD Kit	6-36	*													Power Bits
636TSD140-K	6-36 In-Lbs Torque SD/Boot Kit	6-36	*													Power Bits
1050TSD	10-50 In-Lbs Torque SD	10-50	*													Power Bits
1050TSD-K	10-50 In-Lbs Torque SD Kit	10-50	*													Power Bits
1050TW14I	1/4" SqDr 10-50 In-Lbs TW	10-50	*					*			*				*	
1050TW38NM	3/8" SqDr 10-50 NM, TW	10-50			*			*		*				*		
1050TW38NM-SD	3/8" SqDr 10-50 NM, TW	10-50			*			*		*					*	
1575TW12F	1/2" SqDr 15-75 Ft-Lbs TW	15-75		*					*	*				*		
1575TW12F-CW	1/2" SqDr 15-75 Ft-Lbs TW CW	15-75		*					*			*		*		
1575TW12F-K	1/2" SqDr 15-75 Ft-Lbs TW w BoxSnap Case w/Laser Cut Foam	15-75		*					*	*				*		
1575TW12F-LP	1/2" SqDr 15-75 Ft-Lbs TW LP	15-75		*					*		*			*		
1575TW38F	3/8" SqDr 15-75 Ft-Lbs TW	15-75		*					*					*		
1575TW38F-CW	3/8" SqDr 15-75 Ft-Lbs TW CW	15-75		*					*			*		*		
1575TW38F-CWSD	3/8" SqDr 15-75 Ft-Lbs TW CWSD	15-75		*					*			*			*	
1575TW38F-K	3/8" SqDr 15-75 Ft-Lbs TW w BoxSnap Case w/Laser Cut Foam	15-75		*					*					*		
1575TW38F-LP	3/8" SqDr 15-75 Ft-Lbs TW LP	15-75		*					*		*			*		
1575TW38F-LPSD	3/8" SqDr 15-75 Ft-Lbs TW LPSD	15-75		*					*		*				*	
1575TW38F-SD	3/8" SqDr 15-75 Ft-Lbs TW SD	15-75		*					*						*	
30150TW10MI	30-150 In-Lbs TW, 10MM Rat Hd	30-150	*													10MM GW
30150TW12OI	30-150 In-Lbs TW, 1/2" Rat Hd	30-150	*													1/2" GW
30150TW12F	1/2" SqDr 30-150 Ft-Lbs TW X-Drive Head	30-150		*					*	*				*		
30150TW12F-CW	1/2" SqDr 30-150 Ft-Lbs TW CW X-Drive Head	30-150		*					*			*		*		
30150TW12F-LP	1/2" SqDr 30-150 Ft-Lbs TW LP X-Drive Head	30-150		*					*		*			*		
30150TW13MI	30-150 In-Lbs TW, 13MM Rat Hd	30-150	*													13MM GW
30150TW14I	1/4" SqDr 30-150 In-Lbs TW X-Drive Head	30-150	*					*		*					*	
30150TW14I-CW	1/4" SqDr 30-150 In-Lbs TW CW X-Drive Head	30-150	*					*				*			*	
30150TW14I-LP	1/4" SqDr 30-150 In-Lbs TW X-Drive Head	30-150	*					*			*				*	
30150TW14I-NR	1/4" TW w/NonRatcheting Head X-Drive Head	30-150	*					*							*	
30150TW17MOE	30-150 In-Lbs TW 17MM OE Wr	30-150	*													17MM OE
30150TW38OI	30-150 In-Lbs TW, 3/8" Rat Hd	30-150	*													3/8" GW
30150TW38F	3/8" SqDr 30-150 Ft-Lbs TW X-Drive Head	30-150		*					*					*		
30150TW38F-CW	3/8" SqDr 30-150 Ft-Lbs TW CW X-Drive Head	30-150		*					*			*		*		
30150TW38F-LP	3/8" SqDr 30-150 Ft-Lbs TW LP X-Drive Head	30-150		*					*		*			*		
30150TW38I	3/8" SqDr 30-150 In-Lbs TW X-Drive Head	30-150	*						*					*		
30150TW38I-CW	3/8" SqDr 30-150 In-Lbs TW w/Clock Wise Rotation X-Drive Head	30-150	*						*			*		*		
30150TW38I-K	3/8" SqDr 30-150 In-Lbs TW X-Drive Head w/Box	30-150	*						*					*		
30150TW38I-LP	3/8" SqDr 30-150 In-Lbs TW X-Drive Head	30-150	*						*		*			*		
30150TW38I-NR	3/8" TW w/NonRatcheting Head X-Drive Head	30-150	*						*						*	
30150TW716I	30-150 In-Lbs TW, 7/16" Rat Hd	30-150	*													7/16" GW
30150TW716OE	30-150 In-Lbs TW 7/16 OE Wr	30-150	*													7/16" OE
30150TW916OE	30-150 In-Lbs TW 9/16 OE Wr	30-150	*													9/16" OE
30150TW38I-LPSD	3/8" SqDr 30-150 In-Lbs TW w/LP	30-150	*						*		*				*	
30150TW38I-CWSD	3/8" SqDr 30-150 In-Lbs TW w/Clock Wise Rotation	30-150	*						*			*			*	
30150UTW14I	1/4" SqDr 30-150 In-Lbs TW	30-150	*					*		*					*	
30150UTW14I-CW	1/4" SqDr 30-150 In-Lbs TW CW	30-150	*					*			*				*	
30150UTW14I-LP	1/4" SqDr 30-150 In-Lbs TW	30-150	*					*			*				*	
30150UTW14I-NR	1/4" TW w/NonRatcheting Head	30-150	*					*							*	
30150UTW38I	3/8" SqDr 30-150 In-Lbs TW	30-150	*						*		*				*	
30150UTW38I-CW	3/8" SqDr 30-150 In-Lbs TW w/Clock Wise Rotation	30-150	*						*			*			*	
30150UTW38I-K	3/8" SqDr 30-150 In-Lbs TW w/Box	30-150	*						*		*				*	
30150UTW38I-LP	3/8" SqDr 30-150 In-Lbs TW	30-150	*						*		*				*	
30150UTW38I-NR	3/8" TW w/NonRatcheting Head	30-150	*						*						*	
40200TW12OI	40-200 In-Lbs TW, 1/2" Rat Hd	40-200	*													1/2" GW
40200TW13MI	40-200 In-Lbs TW, 13MM Rat Hd	40-200	*													13MM GW
40200TW14I	1/4" SqDr 40-200 In-Lbs TW	40-200	*					*		*					*	
40200TW14I-LP	1/4" SqDr 40-200 In-Lbs TW LP	40-200	*					*			*				*	
40200TW38OI	40-200 In-Lbs TW, 3/8" Rat Hd	40-200	*													3/8" GW
40200TW38I	3/8" SqDr 40-200 In-Lbs TW	40-200	*						*		*				*	
40200TW38I-CW	3/8" SqDr 40-200 In-Lbs TW CW	40-200	*						*			*			*	
40200TW38I-CWSD	3/8"SqDr 40-200 In-Lbs TW CWSD	40-200	*						*			*			*	
40200TW38I-K	3/8"SqDr 40-200 In-Lbs TW wBox	40-200	*						*		*				*	
40200TW38I-LP	3/8" SqDr 40-200 In-Lbs TW LP	40-200	*						*		*				*	
40200TW38I-LPSD	3/8"SqDr 40-200 In-Lbs TW LPSD	40-200	*						*		*				*	
40200TW38I-SD	3/8" SqDr 40-200 In-Lbs TW SD	40-200	*						*		*				*	
40200TW716I	40-200 In-Lbs TW, 7/16" Rat Hd	40-200	*													7/16" GW
50250TW12OI	50-250 In-Lbs TW, 1/2" Rat Hd	50-250	*													1/2" GW
50250TW13MI	50-250 In-Lbs TW, 13MM Rat Hd	50-250	*													13MM GW
50250TW38OI	50-250 In-Lbs TW, 3/8" Rat Hd	50-250	*													3/8" GW
50250TW38I	3/8" SqDr 50-250 In-Lbs TW	50-250	*						*		*				*	
50250TW38I-CW	3/8" SqDr 50-250 In-Lbs TW CW	50-250	*						*			*			*	
50250TW38I-CWSD	3/8"SqDr 50-250 In-Lbs TW CWSD	50-250	*						*			*			*	
50250TW38I-K	3/8" SqDr 50-250 In-Lbs TWwBox	50-250	*						*		*				*	
50250TW38I-LP	3/8" SqDr 50-250 In-Lbs TW LP	50-250	*						*		*				*	
50250TW38I-LPSD	3/8"SqDr 50-250 In-Lbs TW LPSD	50-250	*						*		*				*	
50250TW38I-SD	3/8" SqDr 50-250 In-Lbs TW SD	50-250	*						*		*				*	
50250TW716I	50-250 In-Lbs TW, 7/16" Rat Hd	50-250	*													7/16" GW
150750TW12I-CW	1/2" SqDr 150-750 In-Lbs TW CW	150-750	*						*		*			*		
150750TW12I	1/2" SqDr 150-750 In-Lbs TW	150-750	*						*	*				*		
150750TW12I-LP	1/2" SqDr 150-750 In-Lbs TW LP	150-750	*						*	*	*			*		
150750TW38I	3/8" SqDr 150-750 In-Lbs TW	150-750	*						*	*				*		
150750TW38I-CW	3/8" SqDr 150-750 In-Lbs TW CW	150-750	*						*	*		*		*		
150750TW38I-K	3/8" SqDr 150-750 IN-Lbs TW w/BoxSnap Case & Laser Cut Foam	150-750	*						*	*		*		*		
150750TW38I-LP	3/8" SqDr 150-750 In-Lbs TW LP	150-750	*						*	*	*			*		
PSTW12OI	1/2" Rat Head Preset In-Lb TW	For Preset	*			*										1/2" GW
PSTW13MI	13MM Rat Head Preset In-Lb TW	For Preset	*			*										13MM GW
PSTW14OI-NR	1/4" SqDr Preset In-Lb TW-NR	For Preset	*			*	*							*		
PSTW22MI	22MM Rat Head Preset In-Lb TW	For Preset	*			*										22MM GW
PSTW38OI	3/8" Rat Head Preset In-Lb TW	For Preset	*			*										3/8" GW
PSTW716I	7/16 Rat Head Preset In-Lb TW	For Preset	*			*										7/16" GW