

Arc Flash Harness Lanyard

6' Arc Flash Energy Absorbing Lanyard Double-leg with Steel Connectors

- Features Kevlar® leg webbing throughout
- Includes pliable Soft Pack energy absorber with Nomex® cover.
- Includes alloy steel snap hook for harness attachment and rebar hooks for anchorage connections
- Double-leg design facilitates 1000# tie-off
- Rebar hooks feature transverse load rated gates



AFHARNES-LANYARD

Specifications

Material

- Webbing: Kevlar®; 5,000 lb min. static strength
- Energy Absorber: Polyester tear-away
- Connectors: Plated alloy steel; 5,000 lb min. static strength with 3,600 lb. gate strength
- Choke-loop: Kevlar®; 5,000 lb min. static strength

Performance

- Static Strength: 5,000 lb min.
- ANSI Lanyard Class: 6' free fall
- Max. Arrest Distance: 48"
- Avg. Arrest Force: 1,800 lb.
- ANSI User Capacity: 130 to 310 lb max.
- OSHA User Capacity: 130 to 425 lb max.

Compliance

- ASTM: F887
- ANSI: Z359.13-2013
- OSHA: 1926.502 and 1910.66



Full Body Harness
Cut Sheet



Full Body Harness
User Instruction Manual