

Box End Wrenches

Cementex Box End Wrenches feature a continuous outer layer of orange insulation to provide a smooth transition between the dual-layer and single-layer portions of each tool. This design makes the working end of the wrenches even slimmer providing a smooth transition and reduced overall size of the wrenches enables access into tighter locations and minimizes the potential of the outer layer being caught on sharp edges that could damage the tools' insulation.



- Newly redesigned and perfected over time
- Slender head allows access to tight locations

Wide range of sizes and length. Custom sizes available.

SAE Options			
Part Number	Size	Part Number	Size
BEW-06	3/16"	BEW-34	1-1/16"
BEW-08	1/4"	BEW-36	1-1/8"
BEW-10	5/16"	BEW-38	1-3/16"
BEW-11	11/32"	BEW-40	1-1/4"
BEW-12	3/8"	BEW-42	1-5/16"
BEW-14	7/16"	BEW-44	1-3/8"
BEW-16	1/2"	BEW-46	1-7/16"
BEW-18	9/16"	BEW-48	1-1/2"
BEW-20	5/8"	BEW-50	1-9/16"
BEW-22	11/16"	BEW-52	1-5/8"
BEW-24	3/4"	BEW-54	1-11/16"
BEW-26	13/16"	BEW-56	1-3/4"
BEW-28	7/8"	BEW-58	1-13/16"
BEW-30	15/16"	BEW-60	1-7/8"
BEW-32	1"	BEW-64	2"


Metric Options

Part Number	Size
BEW-06M	6mm
BEW-07M	7mm
BEW-08M	8mm
BEW-09M	9mm
BEW-10M	10mm
BEW-11M	11mm
BEW-12M	12mm
BEW-13M	13mm
BEW-14M	14mm
BEW-15M	15mm
BEW-16M	16mm
BEW-17M	17mm
BEW-18M	18mm
BEW-19M	19mm
BEW-20M	20mm
BEW-21M	21mm
BEW-22M	22mm
BEW-23M	23mm
BEW-24M	24mm
BEW-25M	25mm
BEW-26M	26mm
BEW-27M	27mm
BEW-28M	28mm
BEW-29M	29mm
BEW-30M	30mm
BEW-32M	32mm

Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V

