

Hex Bit Sockets: 3/8" Square Drive

Cementex Hex Bit Sockets are now available in our standard "Booted" style as well as in our "Flush Connect" configuration. This "Booted" style matches that of our standard sockets and is designed for direct connection to the Cementex X-Drive® ratchets, torque wrenches, and standard extension bars, providing complete coverage of conductive materials.



*Booted style hex bit socket


3/8" Square Drive: Hex Bit Socket SAE Options

Size	3" Length		6" Length	
	Booted	Flush Connect	Booted	Flush Connect
1/8"	IH38-04	IH38-04 WO	IH38-04XL	IH38-04XL WO
9/64"	IH38-4.5	IH38-4.5 WO	IH38-4.5XL	IH38-4.5XL WO
5/32"	IH38-05	IH38-05 WO	IH38-05XL	IH38-05XL WO
3/16"	IH38-06	IH38-06 WO	IH38-06XL	IH38-06XL WO
7/32"	IH38-07	IH38-07 WO	IH38-07XL	IH38-07XL WO
1/4"	IH38-08	IH38-08 WO	IH38-08XL	IH38-08XL WO
5/16"	IH38-10	IH38-10 WO	IH38-10XL	IH38-10XL WO
3/8"	IH38-12	IH38-12 WO	IH38-12XL	IH38-12XL WO
7/16"	IH38-14	IH38-14 WO	IH38-14XL	IH38-14XL WO
1/2"	IH38-16	IH38-16 WO	IH38-16XL	IH38-16XL WO
9/16"	IH38-18	IH38-18 WO	IH38-18XL	IH38-18XL WO
5/8"	IH38-20	IH38-20 WO	IH38-20XL	IH38-20XL WO
3/4"	IH38-24	IH38-24 WO	IH38-24XL	IH38-24XL WO
7/8"	IH38-28	IH38-28 WO	IH38-28XL	IH38-28XL WO

Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V





3/8" Square Drive: Hex Bit Socket Metric Options


Size	3" Length		6" Length	
	Booted	Flush Connect	Booted	Flush Connect
4mm	IH38-04M	IH38-04M WO	IH38-04MXL	IH38-04MXL WO
5mm	IH38-05M	IH38-05M WO	IH38-05MXL	IH38-05MXL WO
6mm	IH38-06M	IH38-06M WO	IH38-06MXL	IH38-06MXL WO
7mm	IH38-07M	IH38-07M WO	IH38-07MXL	IH38-07MXL WO
8mm	IH38-08M	IH38-08M WO	IH38-08MXL	IH38-08MXL WO
9mm	IH38-09M	IH38-09M WO	IH38-09MXL	IH38-09MXL WO
10mm	IH38-10M	IH38-10M WO	IH38-10MXL	IH38-10MXL WO
11mm	IH38-11M	IH38-11M WO	IH38-11MXL	IH38-11MXL WO
12mm	IH38-12M	IH38-12M WO	IH38-12MXL	IH38-12MXL WO
13mm	IH38-13M	IH38-13M WO	IH38-13MXL	IH38-13MXL WO
14mm	IH38-14M	IH38-14M WO	IH38-14MXL	IH38-14MXL WO



Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V

