

Hex T-Handle Wrenches

Solid core T-Handle provides superior grip and rigid construction which limits twisting and flexing and distributed pressure throughout a gloved hand.

Utilizing Cementex double insulation and available in a wide variety of sizes to meet the professional's demands.



SAE Options

Size	6" T-Handle Part Number	9" T-Handle Part Number	14" T-Handle Part Number
5/64"	IHW-564	—	—
3/32"	IHW-332	—	—
7/64"	IHW-764	—	—
1/8"	IHW-180	—	—
9/64"	IHW-964	—	—
5/32"	IHW-532	—	—
3/16"	IHW-316	IHW-316L	IHW-316XL
7/32"	IHW-732	IHW-732L	IHW-732XL
1/4"	IHW-140	IHW-140L	IHW-140XL
5/16"	IHW-516	IHW-516L	IHW-516XL
3/8"	IHW-380	IHW-380L	IHW-380XL
7/16"	IHW-716	IHW-716L	IHW-716XL
1/2"	IHW-120	IHW-120L	IHW-120XL
9/16"	IHW-916	IHW-916L	IHW-916XL
5/8"	IHW-580	IHW-580L	IHW-580XL
3/4"	IHW-340	IHW-340L	—

Metric Options

Size	6" T-Handle Part Number
2mm	IHK-2M
2.5mm	IHK-2.5M
3mm	IHK-3M
4mm	IHK-4M
5mm	IHK-5M
6mm	IHK-6M
7mm	IHK-7M
8mm	IHK-8M
9mm	IHK-9M
10mm	IHK-10M
11mm	IHK-11M
12mm	IHK-12M
13mm	IHK-13M


Wide range of sizes and lengths available

Custom construction available upon request

Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V

