

# Capacitor Discharge Tool

Safely drain the capacitive charge after the circuit is de-energized. Optional resistor available to limit discharge current.



### Capacitor Discharge Tool Includes:

- 24" 1-1/4" O.D. electrically tested (ASTM F-711) fiberglass pole with hand guard
- 1/4" stainless steel hook with 1-3/8" opening
- Grounding Lead — extra flexible No. 2 str. Copper grounding cable with safety yellow neoprene jacket with two hole, tin-plated copper lug terminated on one end in a heat-shrink sleeve
- Ground Clamp and Compression Ferrule sold separately

Part Number	Description
CPCD-1004	Discharge tool with 6' Grounding Lead - 2.7 Lbs.
CPCD-1005	Discharge tool with 8' Grounding Lead - 3.2 Lbs.
CPCD-1006	Discharge tool with 10' Grounding Lead - 3.8 Lbs.
CPCD-1007	Discharge tool with 15' Grounding Lead - 5.2 Lbs.
CPCD-1008	Discharge tool with 20' Grounding Lead - 6.6 Lbs.
CPCD-6735	Add on Resistor Stick (10kV rating, 10 Megohm) - 0.7 Lbs.
CPGC-21575	Aluminum Ground Clamp
CPF-12998	Compression Ferrule