

Hot Stick Instruments: Ammeter

- Designed for use with universal hot sticks.
- Large digital display, numbers are 1" high and 1/2" wide, can be seen 30' to 40' away. Has lighted background for night use.
- For use on low voltage and high voltage lines (tested to 345KV).
- The hold feature captures current readings when applied with telescoping hot sticks from distances.
- 0 - 2000 amp range
- Large digital display, numbers are 1" high and 1/2" wide
- Displays either Hold or Free Run readings
- Accuracy is +/- 1%
- Wide temperature operation -4°F to 104°F (-20°C to 40°C)
- Snap in and out adapter enables the ammeter to be used on conductors up to 2" O.D.
- Low battery indicator
- Weather proof aluminum housing




Ammeter		
Part Number	Description	Weight
CPAM-6790	Hot Stick Instrument: Ammeter	2.4 lbs



Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V